

# 2020 Senoia Raceway Rulebook – Limited Late Model

All drivers must adhere to the general rules, in addition to the division specific rules set forth below.

Senoia Raceway Limited Late Model division allows five engine packages.

---

A.	604 Crate Engine	2250lbs	8" spoiler
B.	Engine Rule	2350lbs	8" spoiler
C.	Engine Rule	2450lbs	8" spoiler
D.	GM/CT525	2400lbs	8" spoiler
E.	NLMS Engine	2400lbs	8" spoiler

---

## ENGINE PACKAGE A – 604 Crate (2250lbs)

---

GM P/N # 19318604–350 CID / 400 HP

GM Engines may be purchased at any GM dealer.

The sealed engines must remain intact and not be tampered with; any seals that have been removed or tampered with will make the engine illegal and not eligible for competition at Senoia Raceway.

No changes are allowed to the engine (intake manifold, heads, valve covers, oil pan, harmonic balancer or any other part /or parts on/or in the engine. Crate Engines must not be altered, modified or changed from factory specs.

No vacuum pumps.

All crate engines must be sealed with factory GM seal bolts or Crate USA seals. We will allow other series seals if we can verify the seal system of the other series.

### CRANKING COMPRESSION

All crate engines will have a maximum cranking pressure of 200 p.s.i. any engine that has over 200 p.s.i. will be illegal to use at Senoia Raceway

# 2020 Senoia Raceway Rulebook – Limited Late Model

---

## ENGINE PACKAGE B – 2350lbs

---

### BLOCK

---

Cast iron V-8 block only.

Maximum cylinder bore size, Chevrolet 4.060, Ford 4.060, Chrysler 4.060.

After-market steel splayed main caps permitted.

Main cap studs and straps permitted.

Deburring block and plugging deck to strengthen block permitted.

Plug or vent and screen oil drain holes in lifter valley permitted.

May surface block.

Lifter bore must be OEM diameter for engine. Chevrolet .840, Ford .875, Chrysler .901.

### CRANK

---

Any steel crank with the exception of (No Pendulum Undercut counterweights and titanium or other Exotic materials.)

Must be standard stroke for engine, Chevrolet 3.480, Chrysler 3.580, Ford 3.500

May balance engine.

### RODS

---

Steel rods only.

No titanium or aluminum rods.

### PISTONS

---

Any flat top pistons and pins.

No dome pistons.

# 2020 Senoia Raceway Rulebook – Limited Late Model

## CAM

---

Solid lift cam only.

No roller, mushroom or radius cams.

## LIFTERS

---

Solid lifters only.

No roller, mushroom or radius lifters.

Lifter retaining tray permitted.

Lifter must be OEM diameter for engine. Chevrolet .840, Ford .875, Chrysler .901

## HEADS

---

These are the only heads permitted.

OEM cast iron straight plug heads,

Chevrolet Bowtie cast iron heads,

Chevrolet Bowtie Vortec cast iron heads,

Dart Iron Eagle cast iron heads,

World Products Sportsman II cast iron heads,

Ford SVO Sportsman cast iron heads,

Chrysler cast iron W-2

Any 23 degree cast iron heads not listed above must be approved by Senoia Raceway for this engine package. Heads may be subject to 50 lb. weight penalty.

All heads must remain AS-CAST.

No cc limit.

Valve angle and spacing must remain original production specs. For heads being used.

Steel valves only. (No titanium valves)

# 2020 Senoia Raceway Rulebook – Limited Late Model

Valve size maximum for (B) engine, Intake-2.020, Exhaust-1.600.

Valve stem diameter 11/32 minimum for all engines.

Under cut stems permitted, any type guides.

Any valve springs, retainers and keepers.

Guide plates, screw in studs and stud girdles permitted.

Roller rocker arms, stud or shaft mount permitted.

No porting or polishing all heads must remain AS-CAST.

No port matching intake or exhaust runners.

Racing valve job permitted, Machine cuts only.

No blending valve job to casting, No deburring intake or exhaust runners.

## TIMING CHAIN

---

Any chain and gears, No gear or belt drives.

## WATER PUMP

---

No electric water pump. Cast or aluminum permitted.

## OIL SYSTEM

---

Wet sump systems, internal or external pumps permitted.

Dry Sump Oil Systems permitted must add an additional 50 lbs.

## FUEL PUMP

---

No electric pump.

# 2020 Senoia Raceway Rulebook – Limited Late Model

## DISTRIBUTOR

---

Any ignition with the exception of magnetos (No magnetos.)

There is a \$300.00 claim rule on all ignition boxes. (See Claim Rule Section for more info.)

## CARBURETOR

---

One four-barrel carburetor only of any manufacturer.

No turbo-chargers, blowers or fuel injections.

All engines must be naturally aspirated.

## INTAKE

---

Any single four-barrel intake permitted.

May port and polish.

Any size carburetor spacer permitted.

ENGINE PACKAGE C – 2450lbs

## BLOCK

---

Cast iron V-8 block only.

Maximum cylinder bore size, Chevrolet 4.060, Ford 4.060, Chrysler 4.060.

After-market steel splayed main caps permitted.

Main cap studs and straps permitted.

Deburring block and plugging deck to strengthen block permitted.

Plug or vent and screen oil drain holes in lifter valley permitted.

May surface block.

# *2020 Senoia Raceway Rulebook – Limited Late Model*

Lifter bore may be oversize.

362.5 Cubic Inch Maximum Ford & Chevrolet.

371.0 Cubic Inch Maximum Chrysler.

## CRANK

---

Any steel crank with the exception of (titanium or other Exotic materials.)

3.500 Maximum stroke for Ford & Chevrolet.

3.580 Maximum stroke for Chrysler.

362.5 Cubic Inch Maximum Ford & Chevrolet.

371.0 Cubic Inch Maximum Chrysler.

## RODS

---

Steel rods only.

No titanium or aluminum rods.

## PISTONS

---

Any pistons and pins.

## CAM

---

Any cam.

## LIFTERS

---

Lifter retaining tray permitted.

Lifters may be oversize.

# 2020 Senoia Raceway Rulebook – Limited Late Model

## HEADS

---

These are the only heads permitted.

Chevrolet : Any 23 degree cast iron heads – Bow Tie, Dart , Pro Action/Pro Top Line/Racing Head Service (RHS) heads. Spark plug location must be the same as the Bow Tie and Dart heads.

Ford: SVO Sportsman cast iron heads M-6049-E351 and M-6049-N352, GT-40-P, World Products Windsor Sr, Pro Action/Pro Top Line/Racing Head Service (RHS) heads.

Chrysler: Cast iron W-2.

All heads must remain AS-CAST.

No cc limit.

Valve angle and spacing must remain original production specs. For heads being used.

Steel valves only. (No titanium valves)

Valve size maximum for (C) engine: Intake – 2.055, Exhaust – 1.625.

Valve stem diameter 11/32 minimum for all engines.

Under cut stems permitted, any type guides.

Any valve springs, retainers and keepers.

Guide plates, screw in studs and stud girdles permitted.

Roller rocker arms, stud or shaft mount permitted.

No porting or polishing all heads must remain AS-CAST.

No Shot Peen porting heads.

No port matching intake or exhaust runners.

Racing valve job permitted – machine cuts only.

No blending valve job to casting.

No deburring intake or exhaust runners.

## INTAKE

---

# 2020 Senoia Raceway Rulebook – Limited Late Model

Any single four-barrel intake permitted.

May port and polish.

Any size carburetor spacer permitted.

## CARBURETOR

---

One four-barrel carburetor only of any manufacture.

No turbo-chargers, blowers or fuel injections.

All engines must be naturally aspirated.

## OIL SYSTEM

---

Wet sump systems, internal or external pumps permitted.

Dry Sump Oil Systems permitted must add an additional 50 lbs.

## WATER PUMP

---

No electric water pump.

## FUEL PUMP

---

No electric fuel pump.

## DISTRIBUTOR

---

Any ignition with the exception of magnetos (No magnetos.)

There is a \$300.00 claim rule on all ignition boxes. (See Claim Rule Section for more info.)

---

ENGINE PACKAGE D – 2450lbs

---



# 2020 Senoia Raceway Rulebook – Limited Late Model

1. 50lbs of bolt on lead must be mounted in front of the rear motor plate. Lead and bolts will be only pieces allowed in making of the 50 lbs. Collars not included.
2. GM Part Number 19271821 (CT525)
3. These engines are sealed at Chevrolet Performance, all engines must have original Chevrolet Performance GM Seals. Engines must not be altered, modified, or changed from factory specifications.
4. The sealed engines must remain intact and not be tampered with. Any seals that have been removed or tampered with will make the engine illegal and not eligible for competition. The penalty for anyone tampering with seals, modifying any internal engine parts, changing the parts from stock as delivered and sealed from the factory will be subject to expulsion from racing at Senoia Raceway.
5. CT525 must run MSD LSX ignition controller. MSD ignition controller must be mounted with easy access for tech inspectors. MSD ignition controller must be programmed with a limit of 7300 RPM maximum
6. When checked after the race, if RPM limit is more than 7300 RPM, this will result in disqualification, no money or points for that race.
7. Original factory seals may not be protested, but claimed for the cost of new engine, CT525 - \$7200 claim, any engine claimed will be turned over as it came in the crate less any bolt on items. Refusal to accept claim will result in disqualification, no money or points for that race.
8. The GM/CT525 will be the only engine allowed to use a coil pack distributorless ignition system.

## CARBURETOR

1. One four barrel carburetor only of any manufacture.
2. Any size carburetor spacer permitted

## Engine Package E

The NLMS engine will be allowed in this engine package. Must have NLMS or Spec stamped in intake runner. 50 pound weight break allowed for full containment seat or head and neck restraint.

*Track reserves the right to change, delete, or amend the rules in the interest of competition.*

# 2020 Senoia Raceway Rulebook – Limited Late Model

## Limited Late Model Rules for ALL Engine Packages

---

### FRAME

---

All frames must be of steel construction.

Square or rectangular frame must have a minimum of 2" by 2" material, .083-wall thickness.

If round tube frame, tubing must have a minimum of 1-3/4" outside diameter, .083 wall thickness.

### WHEEL BASE

---

Minimum wheelbase will be 103" inches.

### ROLL CAGE

---

All cars must have a suitable steel roll cage protecting the driver's compartment, including headrest.

Side roll bars are mandatory, and must extend into the door panels. A minimum of three (3) bars must be used on the left side.

Each bar must be at least 1-1/2" in diameter, with a minimum material thickness of .083".

Roll cages must be welded to frame.

### BODY

---

Same as Super Late Model specs.

### SAFETY

---

Approved helmet and full fire resistant driver's suit required.

50 lbs. weight break for head and neck restraint and/or full containment seat.

All cars must have 3" inch seat belts with shoulder harness and must be attached to roll cage.

*Track reserves the right to change, delete, or amend the rules in the interest of competition.*

# 2020 Senoia Raceway Rulebook – Limited Late Model

We strongly suggest that all cars have an approved fire extinguisher – securely mounted, within easy reach of the driver. A 5 lb. Halon System is recommended.

## NUMBER

---

Number must be at least 18” inches high and on both sides and top of car.

All cars must have a number.

## EXHAUST/MUFFLERS – REQUIRED AT SENOIA RACEWAY

---

Any commercially manufactured muffler – MUST register under 100 decibels.

Collector type headers only.

No modifications and/or alterations to mufflers will be allowed. (No deliberate air leaks, vents, holes, etc.)

Any car that loses a muffler will automatically be disqualified.

Any car that is deemed too loud by track Officials under race conditions will be black-flagged.

## BRAKES

---

Four-wheel disc brakes permitted.

No carbon fiber brake parts permitted.

## FUEL CELL / FUEL

---

An approved fuel cell (32 gallon maximum) must be securely mounted in the trunk area of the car, inside a .20 gauge metal box supported by a minimum of two 2” inch by 1/ 8” inch steel straps.

All fuel cells must be completely visible from rear of car.

Fuel cell must not be mounted lower than bottom of quick-change rear end.

Pump gas or racing fuel only. (RACING FUEL AVAILABLE AT TRACK)

Pump gas may contain up to 10% ethanol as allowed by law.

Gas must pass acid test.

*Track reserves the right to change, delete, or amend the rules in the interest of competition.*

# 2020 Senoia Raceway Rulebook – Limited Late Model

E85 Fuel is allowed.

Fuel must check within 1% at any time checked, (MIN 84%ETHANOL-MAX 86% )

No alcohol, methanol, nitrous oxide, or chemical additives including, but not limited to, propylene oxide, nitro methane, nitro propane, or any nitrate additives.

## TRANSMISSION

---

Must have at least one forward and one reverse gear in working order.

No straight drives or in and out boxes.

## WHEELS

---

Any brand or type of wheel allowed must be mounted with lug nuts.

No knock-off or center lock wheels.

Maximum wheel width-14" inches.

## TIRES

---

Hoosier 1350, 1600, 21 or 55 and American Racer 48,56 allowed.

Grooving, siping, and buffing tires permitted.

All numbers, codes, and manufacturer names must remain visible on the tire. No grinding off of numbers, codes or names. Any tire that has been altered will be illegal.

No tire softeners, or conditioners permitted.

Tires may not be altered using any natural or unnatural, hazardous or nonhazardous, components or chemicals that affect the factory set baseline settings of a given tire.

ALL competitors are subject to tire inspections.

Tires available on race night or call 770-599-6161.

## WEIGHT

---

*Track reserves the right to change, delete, or amend the rules in the interest of competition.*

# 2020 Senoia Raceway Rulebook – Limited Late Model

(A) 604 Crate Engine	2250lbs	8" spoiler
(B) Engine Rule	2350lbs	8"spoiler
(C) Engine Rule	2450lbs	8"spoiler

All cars must have specified weight posted on top left side of roof.

Minimum weight will be measured with driver in car.

Attached weight must be securely bolted to frame with ½" or larger bolts, and painted white or silver with car number clearly painted on them.

No weight may be attached to rear bumper.

No lead pellets or liquid weight.

No driver operated weight adjustment devices.

50 lbs. weight break for head and neck restraint or full containment seat

One pound per lap weight allowance after race.

Track reserves the right to adjust weights in interest of competition should it deem necessary.

## LIMITED LATE MODEL PROTEST FEES

---

Protest fees are as follows:

\$400.00	One Head (No valves will be pulled)
\$300.00	Oil Pan
\$100.00	Engine Setback (1" inch tolerance)
\$100.00	Gas

Any item not listed in the protest fees above is considered a visual protest item and must be protested before race – not after.

---